

14033 Commerce Ave NE Suite 300-405 Prior Lake, MN 55372

Beyond complexity to simplicity.™

April 2014

New Product Announcement

Rodent Repellant Cabling Option – SLX Submersible Transducers

Contegra now offers the SLX 130 Submersible Level Transducer with an optional "Rodent Repellant" [Ropellant™] cable. Ropellant™ cable is available for use with Contegra's two-wire, loop powered milli-amp transducer (i.e. the SLX 130-M or the SLX 130-MIS).

Like Contegra's standard SLX 130 cable, the RopellantTM cable contains a breather tube, a foil shield w/drain wire and a Kevlar® strengthening member. However, the RopellantTM cable contains two insulated conductors and a TPE (Thermoplastic elastomer) jacket. The TPE jacket contains an additive which rodents find to be distasteful/repugnant.

The Ropellant[™] cable's thicker TPE jacket provides excellent electrical isolation. In fact, the Ropellant[™] cable's ability to withstand surges [i.e. the cable's "breakdown voltage"] is superior to the SLX 130's standard three-conductor FEP jacked cable.

Ordering the SLX 130 with the Rodent Repellant cable:

Customers may order the SLX 130 with either the Teflon® (i.e. FEP) or the RopellantTM jacketed cable. The desired jacketing is denoted by the letter 'T' (Teflon) or 'R' (Ropellant) as a suffix to the cable length.

Example: SLX 130-M-10-50**T**-B (emphasis added) **Example:** SLX 130-M-10-50**R**-B (emphasis added)

Includes:

- **SLX 130** submersible transducer
- $\mathbf{M} = 4-20 \text{ mADC output}$
- **10** PSI pressure sensing element
- **50** feet of **T**eflon® (i.e. FEP) signal cable
- **B** = Sealed Breather System.

Includes:

• **SLX 130** submersible transducer

Phone: 651-905-0900

FAX: 651-454-4665

www.Contegra.com

- **M** = 4-20 mADC output
- **10** PSI pressure sensing element
- **50** feet of Ropellant™ signal cable
- B = Sealed Breather System.

Notes:

1. The SLX 130-E/Ek requires three conductors. Therefore only the 'T' selection is available for the SLX 130-E/Ek.

Please call your Contegra Representative for additional information.

Ropellant™ is a trademark of Contegra Inc. Teflon® is a registered trademark of DuPont