# **SUBMERSIBLE**

# LEVEL TRANSDUCER



## MODEL SLX 220a/220b

#### FEATURES

- Loop powered 4-20 mADC output
  - Choice of ranges:
    0-2 feet to 0-60+ feet
- Rugged construction: Lightning & transient protection Chemical resistance
- Field calibration circuit
- Large 2.5" Teflon® diaphragm
- Sealed breather system

#### **APPLICATIONS**

- Sewage Wet Wells
- Sludge Sumps
- Ground Storage Tanks
- Clearwells
- Process Sumps

CONTEGRA'S Model SLX 220a and SLX 220b submersible level transducers reliably measures the level of water, wastewater, or other liquids based upon the hydrostatic pressure of the liquid above the sub-merged sensor's diaphragm. The transducer provides a 4 -20 mADC output signal that is directly proportional to the sensed level.

The Model SLX 220a and SLX 220b provide superior service in demanding level sensing applications such as sewage wet wells, treatment plant level monitoring, etc. Its PVC, Teflon®, PVDF, and Viton® wetted parts provide strong chemical resistance. The isolated, loop powered 4-20 mADC transmitter is accurate and reliable.

The Model SLX 220a provides convenient signal span, offset and in-circuit calibration.

The SLX 220b provides convenient signal span, offset, in-circuit calibration and signal simulation.

The T420 is shown. The T425 is provided with the SLX 220a. The T423 is provided with the SLX 220b.

The SLX 100 is shown. The SLX 130 is provided.



Contegra Inc. 8160 County Rd. 42 W., Suite 300-405, Savage, MN 55372 651-905-0900

# **MODEL SLX 220a / 220b**

0

### Specifications

#### Sensing Element Pressure Ranges (PSI):

- 5 (0 11.5 ft.)
- 15 (0 34.6 ft.)
- 30 (0 69.3 ft.)
- Consult factory for other ranges.
- Accuracy: 0.25% over the full-scale pressure range including nonlinearity, hysteresis, and repeatability.

Overpressure: 4X @ 5 PSI, all others 3X

#### **Compensated Temperature:**

+32° to + 180° F (0° to +82°C) nonfreezing.

- Wetted parts: PVC body, Teflon<sup>®</sup> signal cable and diaphragm, Viton<sup>®</sup> and PVDF sealing components.
- Signal Cable: Teflon® jacket, shielded, Kevlar® support member, breather tube for sealed breather system.
- Input/Output: Loop powered 4-20 mA output,12-28 VDC Class 2 supply into -1000 ohms.

Lead reversal protection.

#### Span Adjustment:

SLX 220a and SLX 220b: From 25-100 % of range. See T425 and T423 for features

Simulation: (SLX 220b Only):

Full range input simulation via on-board pushbutton and potentiometer (SLX 220b). Simulation enables bench calibration and/ or field simulation.

#### Sensor Mechanical: Height - 9",

Diameter - 3.8", Cable Dameter - 0.26" Electrical Connections: Cage clamp-type

barrier terminals for AWG #12-22 Transmitter Enclosure (option):

Nema 4 FRP, lockable

Approvals: Submersible is UL Listed 508

Refer to www.Contegra.com for further specifications and updates including: range availability, entity parameters and barrier information.

## **Engineering Specifications**

A submersible level transducer shall be provided to sense the liquid level of the

at the location as shown on the plan drawings and in accordance with the manufacturer's recommendations. The transmitter shall be a 4-20 mADC, 2-wire, 12 to 28 VDC loop-powered type with its output signal directly proportional to the measured level excursion. The transducer shall be UL Listed.

The transducer housing shall be fabricated of PVC with a 2.5" diameter Teflon® diaphragm. Silicone oil shall be used as a hydraulic fill. The sensor shall provide an output signal directly proportional to the sensed pressure. The sensor shall be mounted using its signal cable and have 3/4" NPT pipe threading for pipe mounting.

The internal air pressure of the sensor assembly shall be relieved to atmospheric pressure through a sealed breather system.

The transmitter shall contain easily accessible calibration and ranging adjustments. Span shall be adjustable from 25-100% of the sensor range. The transmitter shall provide three levels of transient protection on the 4-20 mA loop: a gas tube arrestor for suppression of high voltages, transorbs, and varistors for fast clamping of lower voltage transients. The transmitter's output shall be measurable without disconnecting the loop power. The transducer shall be a CONTEGRA Model (Choose one...) SLX 220a. / SLX 220b



Model	Suffix	Pressure Sensor	Feet of cable	Calibrated Range	Options (not part of UL Listed product)
SLX 220	a = T425 b = T423	XX	XXX	XX	ENCLOSURE A = Nema 4X (w/ breather)
		5 15 30	20 ft. minimum 10 ft. increments	Specific gravity of 1.0 (water)	B = Breather w/o enclosure OTHER M4 = Meter (door mtd. digital

#### \*\* A typical model number is SLX 220a-15-50-16-A

This includes a SLX 130 submersible level transducer with a 15 PSI sensor 50 feet of cable, a Nema 4X enclosure with a T425 transmitter calibrated 4-20 mA over 0-16 feet and a sealed breather system.

Teflon, Viton, and Kevlar are registered trademarks of DuPont. CONTEGRA and Station Master are registered trademarks of Contegra Inc. Specifications are subject to change without notice.

#### Represented by:

## <u>Contegra</u>

Contegra Inc. 8160 County Road 42 W. Suite 300-405 Savage, MN 55378

PHONE: 651-905-0900 FAX: 651-454-4665